

# OSKAR

air products

www.oskarairproducts.com • info@oskarairproducts.com

## Oskar 2040 Fume Arm

101515

- Duct dia.200 mm, reach 4,0 m
- Hood inlet dia.350 mm
- Hanging model

Previous index: • W02-01-2040

### Standard construction:


- nominal airflow 1400-2500 m<sup>3</sup>/h
- all adjustments on the outside
- aluminum hood with air diverter
- grab handle around the hood
- aluminum hood joints
- middle and swivel steel joints
- aluminum and steel mounting swivel
- smooth tubes
- standard built-in air damper
- black PVC flexible hoses (temperature resistance up to 80.°C)
- standard powder coating

### Accessories and options:

- mounting bracket WS-200
- connection flange Ø200 mm steel
- MOD-A set including photosensor, hood light kit, light switch, 8 m of cable
- MOD-L hood light set with switch and 8 m of cable
- MOD-L2 hood light set with 2 switches (additional switch for fan or electric damper control), 8 m of cable
- grounding option - all metal parts hood, tubes, mounting swivel connected with grounding wires
- extended hood Ø200 mm / 500 mm (adds to the price of arm or standard hood)

### Notes

### The method of packing and carton sizes:



A = 390  
B = 2370  
H = 700  
weight = 33 kg

All dimensions are in mm

Menegon Sp z o.o.  
Mokry Dwór 6C 83-021 Wiślnia Polska  
tel.: +48 58 3012838 fax +48 58 3059324  
info@menegon.com.pl www.menegon.com.pl



All rights reserved. This document including constructional and technical information as well as trademarks and brand names are law protected and are property of Menegon Sp. z o.o. The producer reserves the right to introduce changes in construction without prior notification.

