BOXAIR BASIC - MOBILE CASSETTE FILTER

Mobile casette filter unit Boxair Basic is designed for extraction and filtration of welding fumes and dust. Its main features are compact dimensions, solid steel construction and high maneuverability. Boxair Basic mobile filter unit consists of a pre-filter, secondary M5 class filter cartridge and a disposable F9 class main compact filter. The recommended equipment for the Boxair Basic filter unit is the Econ fume extraction arm with a range of 2 meters.


APPLICATION

- sporadic use where there is no need of constant exhaust operation
- dry dusts or fumes capture and filtration especially at welding, grinding, cutting and many more processes (excluding corrosive, chemically aggressive, explosive and flammable gaseous mixtures)

CONSTRUCTION

- aluminium impeller 0,75 kW fan unit
- three stage filtration
- filter indicator
- steel, welded and powder coated construction
- service hour meter
- ready for Econ 160








303.02


TECHNICAL DATA

Airflow	950 m³/h
Fan	0,75 kW
Fan rotation speed	2800 RPM
Standard power supply	1x 230 V +N+PE / 50 Hz, AC
Current rating	5,0 A
Weight without an arm	65,5 kg
Noise level	72 dB(A)
Filtration efficiency	95% @ 0,4 μm
Pre-filter	filtration mat
Secondary filter	M5
Main filter	F9 (6,7 m ²)









All diameters are given in mm

BOXAIR BASIC - MOBILE CASSETTE FILTER

303101540	Mobile filter unit Boxair Basic nominal efficiency 950 m ³ /h, including cassette filters kit, motor 0,75 kW, 230 V, 50 Hz
-----------	---

BOXAIR BASIC- ARMS AND OPTIONS

W02-HA-1620P Hose arm 2 m, hood inlet Ø315 mm

BOXAIR BASIC - SPARE PARTS

Metal mesh spark trap
Filter M5
Cassette filters kit F9
Swivel caster with brake 80
Fixed wheel 80