









	<b>OSKAR</b> air products
	www.oskarairproducts.com • info@oskarairproducts.com
	Stainless Steel Fume Arm - Duct dia.100 mm, reach 1,5 m
	• Hood inlet dia.200 mm. • Standing model.
	Standard construcion:
	<ul> <li>nominal airflow 350-550 m<sup>3</sup>/h</li> <li>all adjustments on the outside</li> <li>atraibace atraibace with back with back with back with the deviation</li> </ul>
	<ul> <li>stainless steel hood with air diverter</li> <li>grab handle around the hood</li> <li>aluminum hood joints</li> </ul>
	<ul> <li>middle and swivel steel joints</li> <li>aluminum and stainless steel mounting swivel</li> </ul>
	<ul> <li>mooth stainless steel tubes</li> <li>stainless steel built-in air damper</li> <li>block DVC flockbla baces (comparative registeres up to 80°C)</li> </ul>
	<ul> <li>black PVC flexible hoses (temperature resistance up to 80°C)</li> <li>grade 304 stainless steel</li> </ul>
	Accessories and options:
	mounting bracket WSS-100 stainless steel     connection flange Ø100mm stainless steel
	<ul> <li>grounding option - all metal parts hood, tubes, mounting swivel connected with grounding wires</li> <li>set of PUR food grade flexible hoses with hygienic certificate</li> </ul>
	<ul> <li>set of electrically conductive flexible hoses</li> <li>hood with light set</li> </ul>
	Notes:
	The method of packing and carton sizes:
	A = 280
	B = 1050 H = 480
	A B weight = 8,5 kg
	All dimensions are given in <b>mm</b> .
	Menegon Sp z o.o.
	Mokry Dwór 6C, 80-021 Wiślina, Polska tel.: +48 58 3012838, fax +48 58 3059324
	info@menegon.com.pl, www.menegon.com.pl
	All rights reserved. This document inlcuding constructional and
CE	technical information as well as Oskar Air Products, Menegon and czystepowietrze.pl trademarks and brand names are law protected and are property of Menegon Sp.o.o.