

OSKAR

air products

www.oskarairproducts.com • info@oskarairproducts.com

Stainless Steel Fume Arm - Duct dia.605 mm, reach 2,0 m

W02-SS-1620P • Hood inlet dia.315 mm.
• Standing model.

Standard construction:


- nominal airflow 900-1400 m³/h
- all adjustments on the outside
- stainless steel hood with air diverter
- grab handle around the hood
- aluminum hood joints
- middle and swivel steel joints
- aluminum and stainless steel mounting swivel
- smooth stainless steel tubes
- stainless steel built-in air damper
- black PVC flexible hoses (temperature resistance up to 80°C)
- grade 304 stainless steel

Accessories and options:

- mounting bracket WSS-160 stainless steel
- mounting bracket WSSD-160 stainless steel (extended version)
- connection flange Ø150mm stainless steel
- connection flange Ø160mm stainless steel
- extended hood Ø160/500mm
- grounding option - all metal parts hood, tubes, mounting swivel connected with grounding wires
- set of PUR food grade flexible hoses with hygienic certificate
- set of electrically conductive flexible hoses
- hood with light set

Notes:

The method of packing and carton sizes:



A = 370
B = 1680
H = 620
weight = 21 kg

All dimensions are given in **mm**.

Menegon Sp z o.o.
Mokry Dwór 6C, 80-021 Wiślina, Polska
tel.: +48 58 3012838, fax +48 58 3059324
info@menegon.com.pl, www.menegon.com.pl

All rights reserved. This document including constructional and technical information as well as Oskar Air Products, Menegon and czystepowietrze.pl trademarks and brand names are law protected and are property of Menegon Sp.o.o.

