



www.oskarairproducts.com • info@oskarairproducts.com

Stainless Steel Fume Arm - Duct dia.200 mm, reach 2,0 m

- W02-SS-2020P · Hood inlet dia.350 mm. Standing model.

Standard construcion:

- efficiency 1400-2500 m³/h
- · all adjustments on the outside
- · stainless steel hood with air diverter
- grab handle around the hood
- aluminum hood joints
- middle and swivel aluminum joints
 aluminum and stainless steel mounting swivel
- smooth stainless steel tubes
- standard built-in air damper
- black PVC flexible hoses (temperature resistance up to 80°C)
- stainless steel grade 304


Accessories and options:

- mounting bracket WSS-200 stainless steel
 connection flange Ø200mm stainless steel
- extended hood Ø200/500mm
- grounding option all metal parts hood, tubes, mounting swivel connected with grounding wires

 set of PUR food grade flexible hoses with hygienic certificate
 set of electrically conductive flexible hoses
 hood with light set

Notes:

The method of packing and carton sizes:



A = 390 B = 1580 H = 700weight = 27 kg

All dimensions are given in mm.

Menegon Sp z o.o. Mokry Dwór 6C, 80-021 Wiślina, Polska tel.: +48 58 3012838, fax +48 58 3059324 info@menegon.com.pl, www.menegon.com.pl

All rights reserved. This document inlcuding constructional and technical information as well as Oskar Air Products, Menegon and czystepowietrze.pl trademarks and brand names are law protected and are property of Menegon Sp.o.o.

