

OSKAR

air products

www.oskarairproducts.com • info@oskarairproducts.com

Oskar 0710P Fume Arm

101490

- Duct dia.75 mm, reach 1,0 m
- Hood inlet dia.160 mm
- Standing model

Previous index: • W02-01-0710P

Standard construction:


- nominal airflow 200-350 m³/h
- all adjustments on the outside
- aluminum hood with air diverter
- grab handle around the hood
- aluminum hood joints
- middle and swivel steel joints
- aluminum and steel mounting swivel
- smooth tubes
- standard built-in air damper
- black PVC flexible hoses (temperature resistance up to 80.°C)
- standard powder coating

Accessories and options:

- mounting bracket WS-075
- connection flange Ø75mm steel
- MOD-L hood light set with switch and 8m of cable
- grounding option - all metal parts hood, tubes, mounting swivel
- connected with grounding wires

Notes

The method of packing and carton sizes:



A = 230 mm
B = 730 mm
H = 330 mm
weight = 5 kg

All dimensions are in mm

Menegon Sp z o.o.
Mokry Dwór 6C 83-021 Wiślnia Polska
tel.: +48 58 3012838 fax +48 58 3059324
info@menegon.com.pl www.menegon.com.pl



All rights reserved. This document including constructional and technical information as well as trademarks and brand names are law protected and are property of Menegon Sp. z o.o. The producer reserves the right to introduce changes in construction without prior notification.

