

# OSKAR

air products

www.oskarairproducts.com • info@oskarairproducts.com

## Oskar 1220P Fume Arm

101500

- Duct dia.125 mm, reach 2,0 m
- Hood inlet dia.250 mm
- Standing model

Previous index: • W02-01-1220P

### Standard construction:


- nominal airflow 550-900 m<sup>3</sup>/h
- all adjustments on the outside
- aluminum hood with air diverter
- grab handle around the hood
- aluminum hood joints
- middle and swivel steel joints
- aluminum and steel mounting swivel
- smooth tubes
- standard built-in air damper
- black PVC flexible hoses (temperature resistance up to 80.°C)
- standard powder coating

### Accessories and options:

- mounting bracket WS-125
- connection flange Ø125mm steel
- MOD-A set including photosensor, hood light kit, light switch, 8 m of cable
- MOD-L hood light set with switch and 8 m of cable
- MOD-L2 hood light set with 2 switches (additional switch for fan or electric damper control), 8 m of cable
- grounding option - all metal parts hood, tubes, mounting swivel connected with grounding wires

### Notes

The method of packing and carton sizes:



A = 330 mm  
B = 1420 mm  
H = 520 mm  
weight = 15,5 kg

All dimensions are in mm

Menegon Sp z o.o.  
Mokry Dwór 6C 83-021 Wiślnia Polska  
tel.: +48 58 3012838 fax +48 58 3059324  
info@menegon.com.pl www.menegon.com.pl



All rights reserved. This document including constructional and technical information as well as trademarks and brand names are law protected and are property of Menegon Sp. z o.o. The producer reserves the right to introduce changes in construction without prior notification.

